



Tadiran T41P

Elegant Business Phone

The Tadiran T41P is a feature-rich SIP phone for business. This 3-Line IP Phone has been designed by pursuing ease of use in even the tiniest details, delivering a superb sound quality as well as rich visual experience. With programmable keys, this phone supports vast productivity-enhancing features, using standard encryption protocols to perform highly secure remote provisioning and software upgrades.

Highlights:

- 2.7" 192x64-pixel graphical LCD with backlight
- LED for call and message waiting indication
- 6 line keys including up to 15 programmable features
- HD Voice: HD Handset, HD Speaker
- 4 context-sensitive "soft" keys
- 5 features keys: message, headset, mute, redial, hands-free speakerphone
- Local phonebook and XML/LDAP remote phonebook
- FTP/TFTP/HTTP/HTTPS/PnP Auto-provisioning
- Dual-color (red or green) illuminated LEDs for line status

Features:

- 3 VoIP accounts
- One-touch speed dial, redial
- Call forward, call waiting, call transfer, call hold
- Call return, group listening
- Mute, auto answer, DND
- Call history: dialed/received/missed/forwarded
- 3-way conference call
- Direct IP call without SIP proxy
- Ringtone selection/import/delete
- Hotline, emergency call
- Set date time manually or automatically
- Dial plan, push XML, action URL



Additional Features:

- Full support of Aeonix feature set
- Integration with Aeonix applications, including Navigator, Attendant Console, Aeonix Dispatch Console, and Aeonix Contact Center
- Busy Lamp Field (BLF), BLF list
- Intercom, paging, music on hold
- Message Waiting Indicator (MWI)
- Anonymous call, anonymous call rejection
- DND & forward synchronization
- N-Way calling, remote office
- Network call logs
- Voice mail, call park, call pickup
- Call recording

Codecs and Voice Features:

- Wideband codec: G.722
- Narrowband codec: G.711, G.723, G.726, G.729AB, GSM
- VAD, CNG, AEC, PLC, AJB, AGC
- Full-duplex hands-free speakerphone with AEC

Physical Features:

- 1xRJ9(4P4C)handsetport/1xRJ9(4P4C)headsetport
- Stand with 2 adjustable angles
- External universal AC Power adapter (optional): AC 100~240V input and DC 5V/1.2A output
- Power over Ethernet (IEEE 802.3af), Class 2, 100 MHZ
- Power consumption (PSU): 1.4-3.9W
- Wall mountable
- Dimensions (WxDxH mm): 212x189x175
- Operating humidity: 10~95%
- Storage temperature: -10 to 50°C

Network and Security:

- SIP v1 (RFC2543), v2 (RFC3261)
- Call server redundancy supported
- NAT transverse: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- SRTP for voice
- Transport Layer Security (TLS)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess
- OpenVPN, IEEE802.1X
- IPv6



About Tadiran:

Tadiran Telecom (TTL) L.P. is a privately held partnership, owned by Afcon Holdings Ltd. and part of the Shlomo Group. It is an established global provider of Unified Communications & Collaboration (UC&C), Contact Center, and Control Room solutions, serving businesses of all sizes, including tier-1 organizations in various market segments in 41 countries worldwide. Tadiran solutions feature a comprehensive family of products including UC platforms, IPPBXs, soft switches, contact centers, Dispatch Console, IP phones and mobility and desktop solutions.

Copyright © 2015 Tadiran Telecom (TTL) L.P. Specifications subject to change without notice. All other products or services mentioned are the trademarks, service marks, registered trademarks or registered service marks of their respective owners.

Visit us at: www.uniquecommunications.com Call us at: Office 1-800-881-8182